





Double Flanged Taper



K=12 Unit: mm

Larger Diameter		Smaller Diameter		L	Weight (kg)				Larger Diameter		Smaller Diameter		L	Weight (kg)			
DN	e <sub>1</sub>	dn	e <sub>2</sub>		PN 10	PN 16	PN 25	PN 40	DN	e <sub>1</sub>	dn	e <sub>2</sub>		PN 10	PN 16	PN 25	PN 40
100	7.2	80	7.0	200	9.3	9.3	9.8	9.8	700	14.4	350	10.2	800	173.5	191.7	-	-
150	7.8	80	7.0	300	14.0	14.0	15.0	17.1	700	14.4	400	10.8	700	168.3	189.0	-	-
	7.8	100	7.2	300	15.0	14.4	15.9	18.0		14.4	450	11.4	700	177.8	201.5	-	-
200	8.4	100	7.2	600	26.9	26.7	29.3	34.6	700	14.4	500	12.0	600	171.4	201.7	-	-
	8.4	150	7.8	300	22.0	21.5	25.0	31.5		14.4	600	13.2	600	195.0	236.0	-	-
250	9.0	150	7.8	600	38.3	37.9	42.8	55.0	800	15.6	400	10.8	1000	253.0	277.8	-	-
	9.0	200	8.4	300	30.0	29.5	35.5	51.0		15.6	450	11.4	800	227.8	255.6	-	-
300	9.6	150	7.8	600	45.4	45.0	51.6	69.2	800	15.6	500	12.0	800	241.2	275.6	-	-
	9.6	200	8.4	600	51.3	46.7	54.4	75.2		15.6	600	13.2	600	224.2	250.7	-	-
350	9.6	250	9.0	300	40.5	39.5	49.0	74.5	900	15.6	700	14.4	600	250.0	285.0	-	-
	10.2	200	8.4	600	56.8	59.7	70.1	-		16.8	450	11.4	1100	322.3	354.8	-	-
400	10.2	250	9.0	600	64.1	62.3	74.5	-	900	16.8	500	12.0	1000	317.2	356.3	-	-
	10.2	300	9.6	300	49.5	52.0	66.0	-		16.8	600	13.2	800	301.1	351.5	-	-
	10.8	200	8.4	600	63.4	68.8	82.2	-		16.8	700	14.4	600	276.0	315.0	-	-
450	10.8	250	9.0	600	70.8	71.4	86.6	-	1000	16.8	800	15.6	600	308.0	352.0	-	-
	10.8	300	9.6	600	78.9	74.6	91.5	-		18.0	500	12.0	1200	412.2	468.9	-	-
	10.8	350	10.2	300	58.0	67.0	86.0	-		18.0	600	13.2	1000	397.6	465.6	-	-
	11.4	250	9.0	600	77.4	85.6	105.0	-		18.0	700	14.4	800	373.6	430.2	-	-
500	11.4	300	9.6	600	85.7	88.8	109.9	-	1100	18.0	800	15.6	600	343.4	404.1	-	-
	11.4	350	10.2	600	92.2	93.6	117.4	-		18.0	900	16.8	600	373.0	438.0	-	-
	11.4	400	10.8	300	67.1	98.3	125.1	-		19.2	600	13.2	1250	529.3	591.8	-	-
600	12.0	250	9.0	700	95.3	110.1	125.7	-	1200	19.2	700	14.4	1050	508.1	559.2	-	-
	12.0	300	9.6	600	94.6	104.2	121.5	-		19.2	800	15.6	860	484.5	539.7	-	-
	12.0	350	10.2	600	101.4	109.0	129.0	-		19.2	900	16.8	800	498.0	557.9	-	-
	12.0	400	10.8	600	110.0	130.0	153.0	-		19.2	1000	18.0	600	453.7	531.2	-	-
600	12.0	450	11.4	300	78.3	118.5	145.7	-	1200	20.4	600	13.2	1530	680.1	770.9	-	-
	13.2	300	9.6	800	138.4	164.5	184.3	-		20.4	700	14.4	1345	668.9	748.3	-	-
	13.2	350	10.2	700	134.7	164.3	186.8	-		20.4	800	15.6	1160	652.3	735.8	-	-
	13.2	400	10.8	600	130.0	150.3	175.8	-		20.4	900	16.8	975	619.6	707.8	-	-
	13.2	450	11.4	600	138.0	155.1	184.8	-		20.4	1000	18.0	790	586.0	692.0	-	-
13.2	500	12.0	600	149.0	190.0	216.0	-	20.4	1100	19.2	605	540.0	640.3	-	-		